

# HEATLOK<sup>®</sup> | HFO

## HIGH LIFT

### SPRAY UP TO AN R-49 IN A SINGLE PASS

Heatlok HFO High Lift, Demilec's first product to leverage ultra-low Global Warming Potential blowing agent, combines an R-value of 7.5 with a 6.5" lift to achieve an R-49 in a single pass. Spray IRC Ceiling insulation code in less time than ever before!



**CLOSED-CELL**



R-value = 7.5/inch\*

Density = 2.2 lb/ft<sup>3</sup>

Ultra-low Global  
Warming Potential



© 2017 Demilec, 3315 E. Division St., Arlington, TX 76011

Phone: 817.640.4900 | Fax: 817.633.2000

Info@Demilec.com | www.Demilec.com

# REDUCED GLOBAL WARMING IMPACT WITH ULTRA-LOW GWP BLOWING AGENT



**CLOSED-CELL**

**Heatlok HFO High Lift** leverages Honeywell's Solstice® Liquid Blowing Agent technology, which has a GWP of 1, 99.9% lower than traditional blowing agents. In compliance with the Montreal Protocol designed to lower the use of global warming potential gasses, Heatlok HFO High Lift combines all of the benefits of Heatlok with the industries fourth generation of blowing agent.

- ⬡ **R-value = 7.5/inch\***
- ⬡ **Spray 6.5" (R-49) in one pass**
- ⬡ **Low VOC emission, meets requirements for schools and healthcare facilities**
- ⬡ **Superior yield, sprayability, adhesion, and reduced gun clogging**
- ⬡ **Formulated with Solstice® Liquid Blowing Agent's Ultra-low GWP of 1**



<b>R-value</b>	7.5/inch*
<b>ASTM E-84</b>	Flame Spread = 12
<b>Temp Range</b>	15 - 100°F (-9 - 38°C)
<b>Yield</b>	4500 - 5000 bd. ft.
<b>Max Lift</b>	6.5 inches

\*Aged R-value at 4 inches per ASTM C518

In compliance with the International Building Code® (IBC), the International Residential Code® (IRC), and the International Energy Conservation Code® (IECC).



© 2017 Demilec. All rights reserved. This product sheet is intended for general information only. Detailed information about our products and services is available online at [www.Demilec.com](http://www.Demilec.com), or by calling 817.640.4900. Rev. May 2017.