

# HEATLOK<sup>®</sup>



## A GREEN SOLUTION IN ONE APPLICATION

Our unique formula incorporates 14% of recycled plastic and renewable oils to create our high-performing, closed-cell polyurethane spray foam insulation. A single application saves time and money in construction costs.



**CLOSED-CELL**

In compliance with the International Building Code<sup>®</sup> (IBC), the International Residential Code<sup>®</sup> (IRC), and the International Energy Conservation Code<sup>®</sup> (IECC).

Density = 2.1 lb/ft<sup>3</sup>

Contains 14% Renewable  
and Recycled Content



3315 E. Division St.  
Arlington, TX 76011  
877.Demilec (877.336.4532)  
817.640.4900  
Info@Demilec.com  
www.Demilec.com



Service Partners  
1029 Technology Park Dr.  
Glen Allen, VA 23059  
804.515.7400  
GeneralInfo@Service-Partners.com  
www.Service-Partners.com

# FIVE BENEFITS WITH ONE APPLICATION



**CLOSED-CELL**

**Heatlok® SP** is our high-performing, versatile spray foam insulation for commercial and residential construction creates a specialized engineered building envelope, which provides better thermal resistance, an excellent air barrier, and a recognized vapor retarder. Demilec continues to strive toward innovative, scientific advancements in high-efficiency spray foam insulation solutions, elastomeric coatings, high-performing quality products, and superior service.

- 
- ⬡ **Air barrier**
  - ⬡ **Insulation**
  - ⬡ **Vapor barrier**
  - ⬡ **Water resistive barrier**
  - ⬡ **Drain plane**

