

SEALECTION[®]



IGNITION BARRIER FREE FOR UNVENTED ATTICS

The same easily applied, open cell spray foam that provides an efficient, life long building envelope is now certified to the same test standards as Icynene's Classic Max and SWD's Quik-Shield 108.

OPEN-CELL

R-value = 3.81 @ 1 inch

Density = 1/2 lb/ft³



© 2015 Demilec, 3315 E. Division St., Arlington, TX 76011
877.Demilec (877.336.4532) | 817.640.4900
Info@Demilec.com | www.Demilec.com

CUTS ENERGY COSTS BY 50%*

OPEN-CELL

Sealection® 500 has been Demilec's flagship product for more than 20 years. This industry leading formula of open cell spray foam insulation expands 120 times its liquid volume to insulate and seal all cracks, gaps, and joints with a single application, and is easy to install and finish. It has now been tested and certified for use in unvented attics without a prescribed ignition barrier. For more information, consult CCRR-1063 on the Demilec website.

*Source: Demilec analysis report of a side-by-side comparison of two identical homes built by Habitat for Humanity; one installed with traditional fiberglass insulation by an anonymous donor, and one installed with Demilec Sealection 500 spray foam insulation donated to Habitat for Humanity.

- 🔧 **Ignition barrier free for unvented attics**
- 🔧 **Maintains performance throughout time and temperature**
- 🔧 **Allows the use of smaller HVAC systems**
- 🔧 **Minimizes outside noise**
- 🔧 **Reduces dust and allergens**

