



APX HAS EVOLVED! MEET THE NEW STANDARD IN FIRE- TEST COMPLIANT OPEN-CELL FOAM

Meet the next generation of open-cell spray foam. Demilec APX 1.2 exceeds the stringent fire-test requirements from the International Building Code. No ignition barrier needed in attics and crawl spaces.

OPEN-CELL

Demilec APX[®] 1.2 is in compliance with the International Building Code[®] (IBC), the International Residential Code[®] (IRC), and the International Energy Conservation Code[®] (IECC).

R-value = 3.7 @ 1 inch
Density = 1/2 lb/ft³
AC 377 Appendix X
Compliant



© 2019 Demilec, 3315 E. Division St., Arlington, TX 76011
Phone: 817.640.4900 | Fax: 817.633.2000
Info@Demilec.com | www.Demilec.com

NO IGNITION BARRIER REQUIRED

OPEN-CELL

Demilec APX 1.2 is used in attics and crawl spaces, and once applied, no ignition barrier is required if the attic is to be used for service of utilities only. If a fire occurs, once the flame is removed from the spray foam insulation, the insulation will not continue to propagate a flame. This superior fire-performing product provides a new standard for fire safety.

Demilec APX 1.2 also provides an air barrier, insulates and seals in one application, and offers superior performance and value.

- ⑥ Reduces energy costs
- ⑥ Reduces outside pollutants
- ⑥ Minimizes outside noise
- ⑥ AC 377 Appendix X compliant
- ⑥ No ignition barrier required
- ⑥ California CA 01350 Low VOC compliant

