

# GEOLOK™



## THE GEOTECHNICAL SOLUTION

Geolok™ is a low-exothermic spray foam designed to stabilize pipelines, manage erosion, and minimize runoff and washout. Geolok will hold pipelines in place and provide support during the construction process.

**CLOSED-CELL**

Geolok can be applied to create a rock shield, which is a large area sprayed over pipes to protect the pipeline during construction and throughout the backfill process.

R-value = 7.36 @ 1 inch

Density = 2 lb/ft<sup>3</sup>



© 2019 Demilec, 3315 E. Division St., Arlington, TX 76011  
Phone: 817.640.4900 | Fax: 817.633.2000  
Info@Demilec.com | www.Demilec.com

# STABILIZATION FOR GEOTECHNICAL APPLICATIONS

CLOSED-CELL

The common practice of laying sandbags during pipeline construction can create hazardous situations for workers navigating the pipeline. **Geolok** is a more efficient application for trench breakers, pillow pads, and rock guards. Safety concerns are minimized since it only takes two workers to apply Geolok - one behind the spray gun, and another to manage the back of the rig. Compared with a multi-man crew needed for difficult manual labor of laying sandbags, Geolok is a more efficient, less hazardous option.

- ⊕ **Install pipe pillows and rock shields faster**
- ⊕ **Diverts water for erosion control**
- ⊕ **Preserves pipeline integrity**
- ⊕ **Fast, durable application**
- ⊕ **No breakdown once backfilled**



© 2019 Demilec. All rights reserved. This product sheet is intended for general information only. Detailed information about our products and services is available online at [www.Demilec.com](http://www.Demilec.com), or by calling 817.640.4900. Rev. Sept. 2019.