

HEATLOK[®] | ABS PRIMER

AIR BARRIER SYSTEM



SAFETY DATA SHEET

SECTION 1: PRODUCT & COMPANY INFORMATION

Manufacturer/Distributor:

Demilec, Inc.

3315 E. Division Street, Arlington, TX 76011

Phone: 817-640-4900 / Fax: 817-633-2000

E-mail: Info@Demilec.com / Website: www.Demilec.com


Use: Self-adhesive membrane primer for porous surfaces.

Product Type: Liquid

For Emergency: CHEMTREC (USA, 24hr) 1-800-424-9300 / CANUTEC (Canada, 24hr) 613-996-6666

SECTION 2: HAZARDS IDENTIFICATION

GHS LABEL ELEMENTS

OSHA/HCS Status	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the Substance or Mixture	Flammable Liquids - Category 2 Skin Corrosion/Irritation - Category 2 Serious Eye Damage/ Eye Irritation - Category 2A Toxic To Reproduction (Fertility) - Category 2 Toxic To Reproduction (Unborn Child) - Category 2 Specific Target Organ Toxicity (Single Exposure) (Narcotic Effects) -Category 3 Specific Target Organ Toxicity (Repeated Exposure) (Bladder, Hearing Organs, Kidneys, Liver, Respiratory System) - Category 2 Aspiration Hazard - Category 1 Aquatic Hazard (Acute) - Category 1 Aquatic Hazard (Long-Term) - Category 1
Hazard Pictograms	
Signal Word	Danger
Hazard Statements	H225 - Highly flammable liquid and vapor. H319 - Causes serious eye irritation. H315 - Causes skin irritation. H361 - Suspected of damaging fertility or the unborn child. H304 - May be fatal if swallowed and enters airways. H336 - May cause drowsiness or dizziness. H373 - May cause damage to organs through prolonged or repeated exposure. (bladder, hearing organs, kidneys, liver, respiratory system) H410 - Very toxic to aquatic life with long lasting effects.
Prevention	P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P241 - Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P233 - Keep container tightly closed. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P260 - Do not breathe vapor. P264 - Wash hands thoroughly after handling.
Response	P391 - Collect spillage. P314 - Get medical attention if you feel unwell. P308 + P313 - IF exposed or concerned: Get medical attention. P304 + P340 + P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P301 + P310 + P331 - IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P302 + P352 + P362+P364 - IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. P332 + P313 - If skin irritation occurs: Get medical attention.

	P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical attention.
Storage	P405 - Store locked up. P403 - Store in a well-ventilated place. P235 - Keep cool.
Disposal	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards Not Otherwise Classified	None known.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Substance/Mixture	Mixture	
Other Means of Identification	Not available	
INGREDIENT NAME	%	CAS Number
Naphtha (petroleum), hydrotreated light	≥25 - ≤50	64742-49-0
Heptane, branched, cyclic and linear	≥25 - ≤50	426260-76-6
Acetone	≥25 - ≤50	67-64-1
n-Hexane	≥10 - ≤25	110-54-3
Heptane	≥10 - ≤25	142-82-5
Toluene	≥10 - ≤25	108-88-3
<p>Heptane and hexane are interchangeable depending on the time of year. Any concentration shown as a range is to protect confidentiality or is due to batch variation. There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.</p>		

SECTION 4: FIRST AID MEASURES

Eye Contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin Contact	Flush contaminated skin with plenty of water. Continue to rinse for at least 20 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

POTENTIAL ACUTE HEALTH EFFECTS

Eye Contact	Causes serious eye irritation.
Inhalation	Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin Contact	Causes skin irritation.
Ingestion	Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

OVER-EXPOSURE SIGNS/SYMPTOMS

Eye Contact	Adverse symptoms may include the following: pain or irritation, watering, redness.
Inhalation	Adverse symptoms may include the following: nausea or vomiting, headache, drowsiness/fatigue, dizziness/vertigo, unconsciousness, reduced fetal weight, increase in fetal deaths, skeletal malformations.
Skin Contact	Adverse symptoms may include the following: irritation, redness, reduced fetal weight, increase in fetal deaths, skeletal malformations.
Ingestion	Adverse symptoms may include the following: nausea or vomiting, reduced fetal weight, increase in fetal deaths, skeletal malformations.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED, IF NECESSARY

Notes to Physician	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific Treatments	No specific treatment.
Protection of First-Aiders	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
See toxicological information (Section 11).	

SECTION 5: FIRE FIGHTING MEASURES

Suitable Extinguishing Media	Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable Extinguishing Media	Do not use water jet or water-based fire extinguishers.
Specific Hazards Arising from the Chemical	Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous Thermal Decomposition Products	Decomposition products may include the following materials: carbon dioxide, carbon monoxide.
Special Protective Actions for Fire-Fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special Protective Equipment for Fire-Fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: ACCIDENTAL RELEASE MEASURES

For Non-Emergency Personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For Emergency Responders	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental Precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
Spill	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

SECTION 7: HANDLING & STORAGE

Protective Measures	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on General Occupational Hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures. Remove contaminated clothing and protective equipment before entering eating areas.
Conditions for Safe Storage, Including Any Incompatibilities	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

SECTION 8: EXPOSURE CONTROL / PERSONAL PROTECTION

CONTROL PARAMETERS - UNITED STATES**OCCUPATIONAL EXPOSURE LIMITS**

Ingredient Name	Exposure Limits
Naphtha (petroleum), hydrotreated light	None.
Heptane, branched, cyclic and linear	ACGIH TLV (United States, 3/2017). TWA: 400 ppm 8 hours. TWA: 1640 mg/m ³ 8 hours. STEL: 500 ppm 15 minutes. STEL: 2050 mg/m ³ 15 minutes.
Acetone	ACGIH TLV (United States, 3/2017). TWA: 250 ppm 8 hours. STEL: 500 ppm 15 minutes. NIOSH REL (United States, 10/2016). TWA: 250 ppm 10 hours. TWA: 590 mg/m ³ 10 hours. OSHA PEL (United States, 6/2016). TWA: 1000 ppm 8 hours. TWA: 2400 mg/m ³ 8 hours.
n-Hexane	ACGIH TLV (United States, 3/2017). Absorbed through skin. TWA: 50 ppm 8 hours. NIOSH REL (United States, 10/2016). TWA: 50 ppm 10 hours. TWA: 180 mg/m ³ 10 hours. OSHA PEL (United States, 6/2016). TWA: 500 ppm 8 hours. TWA: 1800 mg/m ³ 8 hours.
Heptane	ACGIH TLV (United States, 3/2017). TWA: 400 ppm 8 hours. TWA: 1640 mg/m ³ 8 hours. STEL: 500 ppm 15 minutes. STEL: 2050 mg/m ³ 15 minutes. NIOSH REL (United States, 10/2016). TWA: 85 ppm 10 hours. TWA: 350 mg/m ³ 10 hours. CEIL: 440 ppm 15 minutes. CEIL: 1800 mg/m ³ 15 minutes. OSHA PEL (United States, 6/2016). TWA: 500 ppm 8 hours. TWA: 2000 mg/m ³ 8 hours.
Toluene	OSHA PEL Z2 (United States, 2/2013). TWA: 200 ppm 8 hours. CEIL: 300 ppm AMP: 500 ppm 10 minutes. NIOSH REL (United States, 10/2016). TWA: 100 ppm 10 hours. TWA: 375 mg/m ³ 10 hours. STEL: 150 ppm 15 minutes. STEL: 560 mg/m ³ 15 minutes. ACGIH TLV (United States, 3/2017). TWA: 20 ppm 8 hours.

CONTROL PARAMETERS - CANADA**OCCUPATIONAL EXPOSURE LIMITS**

Ingredient Name	Exposure Limits
Heptane, branched, cyclic and linear	CA Alberta Provincial (Canada, 4/2009). 15 min OEL: 2050 mg/m ³ 15 minutes. 8 hrs OEL: 1640 mg/m ³ 8 hours. 8 hrs OEL: 400 ppm 8 hours. 15 min OEL: 500 ppm 15 minutes. CA Ontario Provincial (Canada, 7/2015). TWA: 400 ppm 8 hours. STEL: 500 ppm 15 minutes.
Acetone	CA Alberta Provincial (Canada, 4/2009). 8 hrs OEL: 1200 mg/m ³ 8 hours. 15 min OEL: 1800 mg/m ³ 15 minutes. 8 hrs OEL: 500 ppm 8 hours. 15 min OEL: 750 ppm 15 minutes. CA British Columbia Provincial (Canada, 7/2016). TWA: 250 ppm 8 hours. STEL: 500 ppm 15 minutes. CA Ontario Provincial (Canada, 7/2015). TWA: 500 ppm 8 hours.

	<p>STEL: 750 ppm 15 minutes. CA Quebec Provincial (Canada, 1/2014). TWAEV: 500 ppm 8 hours. TWAEV: 1190 mg/m³ 8 hours. STEV: 1000 ppm 15 minutes. STEV: 2380 mg/m³ 15 minutes. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 750 ppm 15 minutes. TWA: 500 ppm 8 hours.</p>
n-Hexane	<p>CA Alberta Provincial (Canada, 4/2009). Absorbed through skin. 8 hrs OEL: 50 ppm 8 hours. 8 hrs OEL: 176 mg/m³ 8 hours. CA British Columbia Provincial (Canada, 7/2016). Absorbed through skin. TWA: 20 ppm 8 hours. CA Ontario Provincial (Canada, 7/2015). Absorbed through skin. TWA: 50 ppm 8 hours. CA Quebec Provincial (Canada, 1/2014). Absorbed through skin. TWAEV: 50 ppm 8 hours. TWAEV: 176 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). Absorbed through skin. STEL: 62.5 ppm 15 minutes. TWA: 50 ppm 8 hours.</p>
Heptane	<p>CA Alberta Provincial (Canada, 4/2009). 15 min OEL: 2050 mg/m³ 15 minutes. 8 hrs OEL: 1640 mg/m³ 8 hours. 8 hrs OEL: 400 ppm 8 hours. 15 min OEL: 500 ppm 15 minutes. CA British Columbia Provincial (Canada, 7/2016). TWA: 400 ppm 8 hours. STEL: 500 ppm 15 minutes. CA Ontario Provincial (Canada, 7/2015). TWA: 400 ppm 8 hours. STEL: 500 ppm 15 minutes. CA Quebec Provincial (Canada, 1/2014). TWAEV: 400 ppm 8 hours. TWAEV: 1640 mg/m³ 8 hours. STEV: 500 ppm 15 minutes. STEV: 2050 mg/m³ 15 minutes. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 500 ppm 15 minutes. TWA: 400 ppm 8 hours.</p>
Toluene	<p>CA Alberta Provincial (Canada, 4/2009). Absorbed through skin. 8 hrs OEL: 50 ppm 8 hours. 8 hrs OEL: 188 mg/m³ 8 hours. CA British Columbia Provincial (Canada, 7/2016). TWA: 20 ppm 8 hours. CA Ontario Provincial (Canada, 7/2015). TWA: 20 ppm 8 hours. CA Quebec Provincial (Canada, 1/2014). Absorbed through skin. TWAEV: 50 ppm 8 hours. TWAEV: 188 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). Absorbed through skin. STEL: 60 ppm 15 minutes. TWA: 50 ppm 8 hours.</p>
Appropriate Engineering Controls	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental Exposure Controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.
Hygiene Measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/Face Protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Hand Protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body Protection	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Other Skin Protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory Protection	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

SECTION 9: PHYSICAL & CHEMICAL PROPERTIES

Physical State	Liquid
Color	Red
Odor	Solvent (strong)
Odor Threshold	Not Available
pH	Not Available
Melting Point	Not Available
Boiling Point	Not Available
Flash Point	Closed Cup: -9.4°F (-23°C)
Evaporation Rate	Not Available
Flammability (solid, gas)	Not Available
Lower and Upper Explosive (flammable) Limits	Not Available
Vapor Pressure	Not Available
Vapor Density	>1 (air = 1)
Relative Density	0.77
Solubility	Insoluble
Partition Coefficient: n-octanol/water	Not Available
Auto-Ignition Temperature	Not Available
Decomposition Temperature	Not Available
Viscosity	Dynamic (room temperature): 250 mPa•s (250 cP)
Flow Time (ISO 2431)	Not Available
VOC = Volatile Organic Compound	515 g/L

SECTION 10: STABILITY & REACTIVITY

Reactivity	No specific test data related to reactivity available for this product or its ingredients.
Chemical Stability	The product is stable.
Possibility of Hazardous Reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to Avoid	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.
Incompatible Materials	Strong oxidizing and reducing agents, acids, bases, halogenated compounds.
Hazardous Decomposition Products	During a fire, irritating and toxic gases such as carbon monoxide, carbon dioxide and other toxic and irritating compounds such as formaldehyde, methanol, acetic acid, hydrogen peroxide, methane and ethylene oxide may form, depending on the fire conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS - ACUTE TOXICITY

Product/Ingredient Name	Result	Species	Dose	Exposure
Acetone	LD50 Oral	Rat	5800 mg/kg	-
n-Hexane	LC50 Inhalation Gas	Rat	48000 ppm	4 hours
	LD50 Oral	Rat	15840 mg/kg	-
Heptane	LC50 Inhalation Gas	Rat	48000 ppm	4 hours
	LC50 Inhalation Vapor	Rat	103 g/m ³	4 hours
Toluene	LC50 Inhalation Vapor	Rat	49 g/m ³	4 hours

INFORMATION ON TOXICOLOGICAL EFFECTS - IRRITATION/CORROSION

Product/Ingredient Name	Result	Species	Score	Exposure	Observation
Acetone	Eyes - Mild Irritant	Rabbit	-	10 µl	-
	Eyes - Moderate Irritant	Rabbit	-	24 hours, 20 mg	-
	Eyes - Severe Irritant	Rabbit	-	20 mg	-
	Skin - Mild Irritant	Rabbit	-	24 hours, 500 mg	-
	Skin - Mild Irritant	Rabbit	-	395 mg	-
n-Hexane Toluene	Eyes - Mild Irritant	Rabbit	-	10 mg	-
	Eyes - Mild Irritant	Rabbit	-	0.5 minutes, 100 mg	-
	Eyes - Mild Irritant	Rabbit	-	870 µg	-
	Eyes - Severe Irritant	Rabbit	-	24 hours, 2 mg	-
	Skin - Mild Irritant	Pig	-	24 hours, 250 µl	-
	Skin - Mild Irritant	Rabbit	-	435 mg	-
	Skin - Moderate Irritant	Rabbit	-	24 hours, 20 mg	-
Skin - Moderate Irritant	Rabbit	-	500 mg	-	
Sensitization	There is no data available.				
Mutagenicity	There is no data available.				
Carcinogenicity	Product/Ingredient Name	OSHA	IARC	NTP	
	Toluene	-	3	-	
Reproductive Toxicity	There is no data available.				
Teratogenicity	There is no data available.				

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)

Ingredient Name	Category	Target Organs
Naphtha (petroleum), hydrotreated light	Category 3	Narcotic Effects
Heptane, branched, cyclic and linear	Category 3	Narcotic Effects
Acetone	Category 3	Narcotic Effects
n-Hexane	Category 3	Narcotic Effects
Heptane	Category 3	Narcotic Effects
Toluene	Category 3	Narcotic Effects

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE)

Ingredient Name	Category	Target Organs
n-Hexane	Category 2	Not Determined
Toluene	Category 2	Bladder, hearing organs, kidneys, liver and respiratory system

ASPIRATION HAZARD

Name	Result
Heatlok ABS Primer	Aspiration Hazard - Category 1
Naphtha (petroleum), hydrotreated light	Aspiration Hazard - Category 1
Heptane, branched, cyclic and linear	Aspiration Hazard - Category 1
n-Hexane	Aspiration Hazard - Category 1

Heptane	Aspiration Hazard - Category 1
Toluene	Aspiration Hazard - Category 1
Information on the Likely Routes of Exposure	Dermal contact. Eye contact. Inhalation. Ingestion.
POTENTIAL ACUTE HEALTH EFFECTS	
Eye Contact	Causes serious eye irritation.
Inhalation	Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin Contact	Causes skin irritation.
Ingestion	Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.
SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL, AND TOXICOLOGICAL CHARACTERISTICS	
Eye Contact	Adverse symptoms may include the following: pain or irritation, watering, redness.
Inhalation	Adverse symptoms may include the following: nausea or vomiting, headache, drowsiness/fatigue, dizziness/vertigo, unconsciousness, reduced fetal weight, increase in fetal deaths, skeletal malformations.
Skin Contact	Adverse symptoms may include the following: irritation, redness, reduced fetal weight, increase in fetal deaths, skeletal malformations.
Ingestion	Adverse symptoms may include the following: nausea or vomiting, reduced fetal weight, increase in fetal deaths, skeletal malformations.
DELAYED AND IMMEDIATE EFFECTS AND ALSO CHRONIC EFFECTS FROM SHORT AND LONG TERM EXPOSURE	
SHORT TERM EXPOSURE	
Potential Immediate Effects	No known significant effects or critical hazards.
Potential Delayed Effects	No known significant effects or critical hazards.
LONG TERM EXPOSURE	
Potential Immediate Effects	No known significant effects or critical hazards.
Potential Delayed Effects	No known significant effects or critical hazards.
POTENTIAL CHRONIC HEALTH EFFECTS	
General	May cause damage to organs through prolonged or repeated exposure.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	Suspected of damaging the unborn child.
Developmental Effects	No known significant effects or critical hazards.
Fertility Effects	Suspected of damaging fertility.
NUMERICAL MEASURES OF TOXICITY	
Acute Toxicity Estimates	There is no data available.

SECTION 12: ECOLOGICAL INFORMATION

TOXICITY

Ingredient Name	Result	Species	Exposure
Acetone	Acute EC50 7200000 Qg/L Fresh water	Algae - Selenastrum sp.	96 hours
	Acute LC50 6000000 Qg/L Fresh water	Crustaceans - Gammarus pulex	48 hours
	Acute LC50 6900 mg/L Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 5600 ppm Fresh water	Fish - Poecilia reticulata	96 hours
	Chronic NOEC 4.95 mg/L Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.016 ml/L Fresh water	Crustaceans - Daphniidae	21 days
	Chronic NOEC 0.1 ml/L Fresh water	Daphnia - Daphnia magna - Neonate	21 days
n-Hexane	Acute LC50 2500 Qg/L Fresh water	Fish - Pimephales promelas	96 hours
Heptane	Acute LC50 375000 Qg/L Fresh water	Fish - Oreochromis mossambicus	96 hours
Toluene	Acute EC50 11600 Qg/L Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
	Acute EC50 6000 Qg/L Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Chronic NOEC 2 mg/L Fresh water	Daphnia - Daphnia magna	21 days
Persistence and Degradability	There is no data available.		

BIOACCUMULATIVE POTENTIAL			
Ingredient Name	LogPow	BCF	Potential
Naphtha (petroleum), hydrotreated light	2.2 to 5.2	10 to 2500	High
Acetone	-0.23	-	Low
n-Hexane	4	501.187	High
Heptane	4.66	552	High
Toluene	2.73	90	Low
MOBILITY IN SOIL			
Soil/Water Partition Coefficient (Koc)	Not available.		
Other Adverse Effects	No known significant effects or critical hazards.		







SECTION 13: DISPOSAL CONSIDERATION

Disposal Methods	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
------------------	--

UNITED STATES - RCRA TOXIC HAZARDOUS WASTE "U" LIST

Ingredient Name	CAS #	Status	Reference Number
Toluene	108-88-3	Listed	U220
Acetone	67-64-1	Listed	U002

SECTION 14: TRANSPORTATION INFORMATION

	DOT Classification	TDG Classification	IMDG	IATA
UN Number	UN1133	UN1133	UN1133	UN1133
UN Proper Shipping Name	ADHESIVES	ADHESIVES. Marine pollutant (Naphtha (petroleum), hydrotreated light, Heptane, branched, cyclic and linear)	ADHESIVES. Marine pollutant (Naphtha (petroleum), hydrotreated light, Heptane, branched, cyclic and linear)	ADHESIVES
Transport Hazard Class(es)	3 	3  	3  	3 
Packing Group	II	II	II	II
Environmental Hazards	No	Yes	Yes	Yes. The environmentally hazardous substance mark is not required.

AERG: 128

DOT-RQ DETAILS

Toluene	1000 lbs / 454 kg (137.86 gal / 521.84 L)
Acetone	5000 lbs / 2270 kg (758.12 gal / 2869.8 L)

ADDITIONAL INFORMATION

DOT Classification	Reportable quantity 8433.5 lbs / 3828.8 kg (1313.6 gal / 4972.5 L). Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements. Special provisions: 383.
TDG Classification	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3), 2.7 (Marine pollutant mark). The marine pollutant mark is not required when transported by road or rail.

IMDG	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. Emergency schedules F-E, S-D
IATA	The environmentally hazardous substance mark may appear if required by other transportation regulations.
Special Precautions for User	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

SECTION 15: REGULATORY INFORMATION

U.S. Federal Regulations	TSCA 8(a) PAIR: Heptane; 2-Methoxy-1-methylethyl acetate TSCA 8(a) CDR Exempt/Partial exemption: Not determined United States inventory (TSCA 8b): All components are listed or exempted. Clean Water Act (CWA) 307: Toluene Clean Water Act (CWA) 311: Toluene; Xylene
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	Listed
Clean Air Act Section 602 Class I Substances	Not Listed
Clean Air Act Section 602 Class II Substances	Not Listed
DEA List I Chemicals (Precursor Chemicals)	Not Listed
DEA List II Chemicals (Essential Chemicals)	Listed

SARA 302/304

Composition/Information on Ingredients	No products were found.
SARA 304 RQ	Not applicable

SARA 311/312

Classification	Flammable Liquids - Category 2 Skin Corrosion/Irritation - Category 2 Serious Eye Damage/ Eye Irritation - Category 2A Toxic To Reproduction (Fertility) - Category 2 Toxic To Reproduction (Unborn Child) - Category 2 Specific Target Organ Toxicity (Single Exposure) (Narcotic Effects) - Category 3 Specific Target Organ Toxicity (Repeated Exposure) (Bladder, Hearing Organs, Kidneys, Liver, Respiratory System) - Category 2 Aspiration Hazard - Category 1
----------------	--

COMPOSITION/INFORMATION ON INGREDIENTS

Naphtha (petroleum), hydrotreated light	Flammable Liquids - Category 2 Skin Corrosion/Irritation - Category 2 Specific Target Organ Toxicity (Single Exposure) (Narcotic Effects) - Category 3 Aspiration Hazard - Category 1
Heptane, branched, cyclic and linear	Flammable Liquids - Category 2 Skin Corrosion/Irritation - Category 2 Specific Target Organ Toxicity (Single Exposure) (Narcotic Effects) - Category 3 Aspiration Hazard - Category 1
Acetone	Flammable Liquids - Category 2 Serious Eye Damage/ Eye Irritation - Category 2A Specific Target Organ Toxicity (Single Exposure) (Narcotic Effects) - Category 3
n-Hexane	Flammable Liquids - Category 2 Skin Corrosion/Irritation - Category 2 Serious Eye Damage/ Eye Irritation - Category 2A Toxic To Reproduction (Fertility) - Category 2 Specific Target Organ Toxicity (Single Exposure) (Narcotic Effects) - Category 3 Specific Target Organ Toxicity (Repeated Exposure) - Category 2 Aspiration Hazard - Category 1
Heptane	Flammable Liquids - Category 2 Skin Corrosion/Irritation - Category 2 Specific Target Organ Toxicity (Single Exposure) (Narcotic Effects) - Category 3 Aspiration Hazard - Category 1
Toluene	Flammable Liquids - Category 2 Skin Corrosion/Irritation - Category 2 Serious Eye Damage/ Eye Irritation - Category 2A Toxic To Reproduction (Unborn Child) - Category 2 Specific Target Organ Toxicity (Single Exposure) (Narcotic Effects) - Category 3 Specific Target Organ Toxicity (Repeated Exposure) (Bladder, Hearing Organs, Kidneys, Liver, Respiratory System) - Category 2 Aspiration Hazard - Category 1

SARA 313		
	Product Name	CAS Number
Form R - Reporting Requirements	n-Hexane Toluene	110-54-3 108-88-3
Supplier Notification	n-Hexane Toluene	110-54-3 108-88-3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

STATE REGULATIONS

Massachusetts	The following components are listed: n-Hexane; Heptane; Toluene; Acetone
New York	The following components are listed: n-Hexane; Toluene; Acetone
New Jersey	The following components are listed: n-Hexane; Heptane; Toluene; Acetone
Pennsylvania	The following components are listed: n-Hexane; Heptane; Toluene; Acetone
California Prop. 65	WARNING: This product can expose you to chemicals including Toluene, N-methyl-2-pyrrolidone, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov .

CANADA - CANADIAN LISTS

Canadian NPRI	The following components are listed: Heptane, branched, cyclic and linear; n-Hexane; Heptane; Toluene; Acetone
CEPA Toxic Substances	The following components are listed: Acetone
Canada Inventory (DSL NDSL)	All components are listed or exempted.

SECTION 16: OTHER INFORMATION

PROCEDURE USED TO DERIVE THE CLASSIFICATION

Classification	Justification
Flammable Liquids - Category 2	On basis of test data
Skin Corrosion/Irritation - Category 2	Calculation method
Serious Eye Damage/Eye Irritation - Category 2A	Calculation method
Toxic To Reproduction (Fertility) - Category 2	Calculation method
Toxic To Reproduction (Unborn Child) - Category 2	Calculation method
Specific Target Organ Toxicity (Single Exposure) (Narcotic Effects) - Category 3	Calculation method
Specific Target Organ Toxicity (Repeated Exposure) (Bladder, Hearing Organs, Kidneys, Liver, Respiratory System) - Category 2	Calculation method
Aspiration Hazard - Category 1	Expert Judgement
Aquatic Hazard (Acute) - Category 1	Calculation method
Aquatic Hazard (Long-Term) - Category 1	Calculation method

HISTORY

Date of Issue (mm/dd/yyyy)	04/30/2018
Date of Previous Issue	Not applicable
Version	1
Prepared By	KMK Regulatory Services Inc.
Notice to Reader	To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.