

HEATLOK® | ABS PRIMER

AIR BARRIER SYSTEM



TECHNICAL DATA SHEET

Heatlok® ABS Primer is a primer specifically designed to enhance the adhesion of self-adhesive Heatlok ABS wall membranes on porous surfaces such as exterior gypsum boards at temperatures above -22°F (-30°C). It is composed of SBS synthetic rubbers, adhesive enhancing resins and volatile solvents.

RECOMMENDED SUBSTRATES

This product can be used on exterior gypsum boards, wood, metal and concrete.

APPLICATION

Heatlok ABS Primer can be applied with a brush or a roll on dry and clean substrates. It must be thoroughly dry before applying the waterproofing membrane. Heatlok ABS Primer must be well shaken before use.

WARNING: KEEP AWAY FROM ALL FLAME OR SPARK SOURCES WHEN HEATLOK ABS PRIMER IS DRYING.

For complete information on product application, please consult your Demilec representative.

PACKAGING	
Specifications	Heatlok ABS Primer
Physical State	Liquid
Color	Orange
Specific Gravity @ 68°F (20°C)	0.79 kg/L
Solids by Weight	24%
Viscosity, Brookfield @ 77°F (25°C)	200 cP
Containers	5.0 gal (19 L) 1.0 gal (3.78 L)
Coverage applied with a brush or roll	Porous Surfaces 0.3 - 0.5 L/m ² Non-Porous Surfaces 0.1 - 0.25 L/m ²
Coverage applied with spray equipment	Porous Surfaces 0.15 - 0.21 L/m ² Non-Porous Surfaces 0.07 - 0.1 L/m ²
Drying time for application with a brush or roll	15 - 60 mins, depending on temperature and quantity applied
Drying time for application with spray equipment	5 - 10 mins, depending on temperature and quantity applied

(All values are nominal)

STORAGE & HANDLING

Shelf life: Up to 60 months in original sealed containers. Store in a well ventilated area < 95°F (35°C). Keep away from any source of heat, dampness, humidity, oxidizing agents or direct sunlight. Flammable before curing. Keep away from sources of ignition. Tools and equipment can be cleaned with petroleum solvents such as mineral spirits, varsol, xylene, etc.

For more information, refer to instructions on the container label and relevant safety data sheet (SDS).