

HEATLOK[®]



CLOSED-CELL FOAM DESIGNED FOR THE BUILDING ENVELOPE

Heatlok Eco offers a robust closed-cell spray foam insulation, providing a consistent, comfortable living space.



CLOSED-CELL

R-value = 6.5 @ 1 inch
R-value = 21 @ 3.1 inches
Density = 2.0 lb/ft³



© 2018 Demilec, 3315 E. Division St., Arlington, TX 76011
Phone: 817.640.4900 | Fax: 817.633.2000
Info@Demilec.com | www.Demilec.com

ENHANCED SPRAYABILITY WITH HEATLOK ECO



CLOSED-CELL

In today's economy, contractors must choose a consistent product that can compete financially and meet the minimum code requirements for the building envelope. Heatlok Eco is the smart choice with the performance needed for a job well done.

- ⑥ **Spray 2" + 2" or 3.25" lifts**
- ⑥ **Achieve an R-value of 21 @ 3.1 inches**
- ⑥ **Designed for interior application**
- ⑥ **Summer and Winter for varying temperatures**

	Heatlok Eco
R-value @ 1 inch	6.5
ASTM E-84	Flame Spread < 25
Storage Temp	50 - 100°F (10 - 38°C)
Yield	4300 bd. ft.
Max Lift	2" + 2" or 3.25"



In compliance with the International Building Code® (IBC), the International Residential Code® (IRC), and the International Energy Conservation Code® (IECC).



© 2018 Demilec. All rights reserved. This product sheet is intended for general information only. Detailed information about our products and services is available online at www.Demilec.com, or by calling 817.640.4900. Rev. September 2019.