

HEATLOK®



PRO



SUPERIOR YIELD AND INDUSTRY LEADING R-VALUE

Heatlok® HFO Pro, with an R-value of 7.4 at 1 inch, is designed as a continuous insulation solution with an ultra-low global warming potential blowing agent. Tested and certified as an air barrier, vapor retarder, water barrier and thermal insulation.



CLOSED-CELL

R-value = 7.4/inch @ 1 inch
R-11 @ 1.5 inches

Density = 2.2 lb/ft³

Ultra-low Global Warming Potential

19% Recycled & Renewable Content



© 2019 Demilec, 3315 E. Division St., Arlington, TX 76011

Phone: 888-261-7705 | Fax: 817.633.2000

BuildingScience@Demilec.com | www.Demilec.com

COMBINES THE STRENGTHS OF HEATLOK WITH THE INDUSTRIES 4th GENERATION OF BLOWING AGENT



CLOSED-CELL

Heatlok HFO Pro leverages Honeywell's Solstice® Liquid Blowing Agent technology, which has a GWP of 1, 99.9% lower than traditional blowing agents. In compliance with the Montreal Protocol designed to lower the use of global warming potential gasses.

- ⊕ R-value = 7.4/inch @ 1 inch
R-11 @ 1.5 inches
- ⊕ Passes NFPA 285 with brick, stone, and masonry exterior.
- ⊕ 20% yield increase and improved flame spread over Heatlok Soy 200 Plus
- ⊕ Class II vapor retarder at 1 inch
- ⊕ 5% more recycled & renewable content than Heatlok Soy 200 Plus
- ⊕ Exceeds ASHRAE 90.1 continuous insulation requirement at 1.5 inches
- ⊕ Superior adhesion and compressive strength
- ⊕ ABAA Certified



In compliance with the International Building Code® (IBC), the International Residential Code® (IRC), and the International Energy Conservation Code® (IECC).

| | |
|---------------------------|---|
| B-value | 7.4/inch @ 1 inch |
| ASTM-E 84 | Flame Spread Index = 12 / Smoke Developed = 350 - 400 |
| Application Temp Range | 15 - 100°F (-9 - 38°C) |
| Yield | 5,000 bd. ft. / set |
| Max Single Pass Thickness | 2" + 2" |
| Certification | Evaluation Report 565 |



© 2019 Demilec. All rights reserved. This product sheet is intended for general information only. Detailed information about our products and services is available online at www.Demilec.com, or by calling the Building Science Dept. at 888-261-7705. Rev. Sept. 2019.