

# HEATLOK<sup>®</sup> | XT

## HIGH LIFT

**SPRAY UP TO  
4 INCHES THICK  
IN ONE PASS**

Save time and money on the jobsite with Demilec's Heatlok XT High Lift. This innovative new foam can be sprayed up to 4" thick, achieving the required R-value in fewer passes.



**CLOSED-CELL**

Density = 2.17 lb/ft<sup>3</sup>  
Contains >20% Renewable  
and Recycled Content

© 2019 Demilec, 3315 E. Division St., Arlington, TX 76011  
Phone: 817.640.4900 | Fax: 817.633.2000  
Info@Demilec.com | www.Demilec.com

 **DEMILEC**

# EARN UP TO 10 LEED POINTS WITH >20% RENEWABLE & RECYCLED CONTENT

**Heatlok XT High Lift** is our high-performing, versatile, closed cell spray foam insulation for commercial and residential construction. It creates a specially engineered building envelope that provides better thermal resistance, an excellent air barrier, and a recognized vapor retarder.

- >20% recycled & renewable content**
- Up to 10 LEED points\***
- 0-5 flame spread based on ASTM E-84**
- Interior and exterior applications**
- Low exo-therm reaction**

\*Dependent on job distance from manufacturer.

	Summer	Winter
R-value @ 1 inch	6.7	6.9
ASTM E-84	Flame Spread = 0-5	Flame Spread = 5
Temp Range	50 - 100°F (10 - 38°C)	10 - 50°F (-12 - 10°C)
Yield	4500 - 5000 bd. ft.	
Max Lift	4 inches	

**CLOSED-CELL**



In compliance with the International Building Code® (IBC), the International Residential Code® (IRC), and the International Energy Conservation Code® (IECC).



© 2019 Demilec. All rights reserved. This product sheet is intended for general information only. Detailed information about our products and services is available online at [www.Demilec.com](http://www.Demilec.com), or by calling 817.640.4900. Rev. Sept. 2019.